

AVANTE
GLOBAL TRADES



Collection

2024

300X
1200MM | 11
MM

**300X
1200MM**


THICKNESS

11MM

FEATURES



- Weather resistant.



- High tensile strength.



- Stress-resistant.



- Frost and fire-resistant.

**GLORIOUS LOOK THAT
STUNS EVERYONE.**






DENSE COFFEE

FULLBODY
TILES



DENSE GREY



DENSE NEGRO



DENSE CREMA



DENSE COFFEE



DENSE SAHARA



DENSE VERDE



DENSE LUX

300X1200MM
11 MM THICKNESS

SURFACES
SATIN

FULLBODY
TILES



GLIMPSE BLACK



GLIMPSE WHITE



GLIMPSE BLACK

300X1200MM
11 MM THICKNESS

SURFACES
SATIN



GLIMPSE WHITE

TECHNICAL SPECIFICATION

Dimension and Surface Quality	Test Method	Require	Result
Deviation in Length (l) & Width (w)	ISO 10545 - 2	± 1mm	0.00 mm
Thickness	ISO 10545 - 2	± 0.5mm	0.00 mm
Straightness of sides	ISO 10545 - 2	± 0.8mm	0.09 mm
Rectangularity	ISO 10545 - 2	± 1.5mm	0.11 mm

Physical Property

Water Absorption %	ISO 10545 - 3	Less then 0.5	0.044 %
Breaking Strength	ISO 10545 - 4		7194.95 N
Modulus of Rupter (MOR)N/mm’	ISO 10545 - 4	35	49.06 N/mm2
Resistance to surface abrasion	ISO 10545-7		PEI Class - III 1500 Revolution pass
Coefficient of Liner Thermal Expansion	ISO 10545 - 8	9X10-6 Max	5.51x10-6
Thermalshock Resis	ISO10545 - 9	10 Cycle, Min	Confirm
Crazing Resistance	ISO 10545-11	No Crazin in Two Cycle	Confirm
Moisture Expansion (in mm/mm)	ISO 10545 -10	0.02 mm/m max	0.01 mm/m max
Impact resistance	ISO 10545 - 5	0.55 Min	0.78
Scrach hardness of Srface	ISO 13630 - 13	5 moh's scal	5 Moh's
Bulk density, lin (g/cc)	ISO 10545 - 3	2.2 m'n	2.2903 glcc

Chemical Property

Resistance to Stain	ISO 10545-14	Min Class - 3	Class - 5
Resistance to Low Concentration of acid and alkali	ISO 10545-13	Min Class-GLC	Class GLA

Packaging Details:

SIZE	THICKNESS	FINISH
300x1200mm	11MM	Matt

AVG WEIGHT	NO. TILES/BOX	COVERAGE /BOX
36	4 pcs	1.44 sq. mtr 15.5 sq ft